



## Fos-stik™



### Professional aerosol spray adhesive

- Multipurpose adhesive
- Fast Tack
- Contains no dichloromethane or CFC's and HCFC's
- Powerful, durable bond



### **FOS-STIK™**

FOS-STIK™ is a professional aerosol adhesive for easy, clean, economical adhesion of a large range of materials. It is economical in use, has a foaming formula (low soak in) and adjustable spray nozzle. Fos-Stik™ contains no dichloromethane or CFC's and HCFC's and will produce a powerful, durable bond.

#### **Adhesion**

Professional aerosol adhesive, for fast, clean adhesion of:  
Plastics (compatibility to be tested), rubber, foam and mineral fibre insulants, paper, fabrics, cork, carpeting, etc., either to themselves or onto substrates of metal (not on copper or zinc), wood, concrete, etc..

#### **Advantages**

FOS-STIK™ offers many advantages to conventional methods of adhesion:

- Powerful, durable bond
- Foaming formula, low "soak-in"
- Economical use
- No hardened brushes
- Adjustable nozzle ('Low', 'Medium' or 'High' settings; vertical or horizontal spray-fan)
- Easy to use
- Permanent or temporary bonding

#### **Application**

Permanent bond:

If one surface is porous, apply FOS-STIK™ to one side only and press surfaces firmly together.  
For 2 non-porous surfaces, apply FOS-STIK™ to both sides, allow 5-10 minutes open time and then bring surfaces together firmly.

Temporary bond, or with self-adhesive properties:

Apply FOS-STIK™ to one side only. After 3-5 minutes "open time" it has self-adhesive properties.

#### **Technical Data**

Composed of	Styrene Butadiene Rubber (SBR) in solvent
Coverage	Area (Dry layer 36 tot 18 gm/ m <sup>2</sup> ): 2,5 to 5 m <sup>2</sup> - 25 mm/ can Strip (25mm wide): 100 - 200 lin. m
Application temperature	+5 to +30°C
Operating temperature	-10 to +40°C
Colour	Yellow/ gold
Solids content	ca. 25% (weight)
Container	Aerosol
Storage limits	In clean, dry, dark space at +5 to +25°C In unopened packing for 12 months